

## REFRIGERATED COMPRESSED AIR DRYER

**MODEL:**

**D600IN-A 230/1/50**

Rated capacity\*

<b>Flow rate</b>	m <sup>3</sup> /h	600	
	l/min	10000	
	cfm	353,4	
<b>Inlet air temperature</b>	°C / °F	35 / 95	(Min 5 / 41 ÷ Max 60 / 140)
<b>Outlet air temperature</b>	°C / °F	27 / 81	(Max 40 / 104)
<b>Ambient temperature</b>	°C / °F	25 / 77	(Min 2 / 36 ÷ Max 50 / 122)
<b>Working pressure</b>	bar / psi	7,0 / 101,5	(Min 3 / 44 ÷ Max 16 / 232)
<b>Pressure drop</b>	bar / psi	0,17 / 2,47	(Max 0,34 / 4,93)
<b>Pressure dew point</b>	°C / °F	3 / 37	
<b>Power supply</b>	V/Ph/Hz	230/1/50	(±10% / -- / ±1)
<b>Rated power consumption</b>	kW	1,01	(Max 1,26)
<b>Rated adsorption</b>	A	5,25	(Max 5,68)
<b>Lock Rotor Ampere</b>	A	31	
<b>Condenser cooling air flow rate</b>	m <sup>3</sup> /h	2800	
<b>Condenser max heat rejection</b>	kW	6	
<b>Weight</b>	kg / Lbs	134 / 295	
<b>Air connections</b>	IN/OUT	2" BSP	
<b>Coolant type</b>	Freon / kg / t CO <sub>2</sub>	R513A / 1,40 / 0,884	

### Standard features

<b>Control panel:</b>	Electronic system type	<b>Separator type:</b>	Demister type
<b>Condenser cooling:</b>	Air cooled	<b>Compressor type:</b>	Hermetic type
<b>Ventilator motor:</b>	Suction fan	<b>Installation location:</b>	Indoor
<b>Heat exchanger:</b>	Aluminium brazed plate	<b>Drain discharge:</b>	No loss drain
<b>Expansion method:</b>	Capillary tube + by-pass	<b>Electric protection:</b>	IP 42

\* Performances refer to air suction of FAD 20°C (68°F), 1 bar (14.5 psig), and the following operating conditions: 7 bar (100 psig) working pressure, 3°C (37°F) pressure dewpoint, 25°C (77°F) ambient temperature, 35°C (95°F) compressed air inlet temperature.

Performances & specifications: +/- 5%

